

---

## Contractor Foam Gun Applicator – Instructions and Maintenance

### Step-by-Step Instructions:

- Before putting a can of foam on the gun for the first time, press the trigger down to release any air that may be in the barrel
- Shake the foam pressure-pack can and screw the can to the gun. DO NOT OVERTIGHTEN.
- Squeeze the trigger to allow the foam to fill the barrel
- Adjust the flow by tightening or loosening the flow-adjustment screw found at the back of the gun
- For best results, mist the area to be foamed with water first. The hygroscopic foam setting process is aided with water dampness of the substrate.
- When finished, tighten the flow-adjustment screw fully until the trigger is locked

### Maintenance:

- **Always keep a can on the gun. Failure to do so will cause the foam to harden in the gun barrel to permanently clog the gun**
- The nozzle tip can be cleaned using a wire brush or similar. DO NOT scrape on a rough surface such as the concrete footpath bricks or rocks
- When changing over cans we recommend squirting **Foam Professional Gun Cleaner - 22011** into the can receiver inlet of the gun to free up any foam and prevent the inlet from blocking
- If you prefer to clean the gun between jobs, ready for the next new spray can or the gun barrel is blocked, attach a can of **Foam Professional Gun Cleaner - 22011** to flush out the barrel
- If the ball valve, located in the gun where the can is attached, becomes stuck, use a thin object such as a pencil to press down on the ball to release it



(07) 5446 7963



[www.aquascapesupplies.com.au](http://www.aquascapesupplies.com.au)  
[office@aquascapesupplies.com.au](mailto:office@aquascapesupplies.com.au)



21 Progress Place  
Yandina QLD 4561, Australia